

>>Datasheet<<

ECS-T351



Overall Specifications

Technical Information	
processor	11th generation Tiger Lake processors support : Intel Core™ i3- 1115G4, 2C4T, up to 4.1 GHz Intel Core™ i3- 1125G4, 4C8T, up to 3.7 GHz Intel Core™ i5 - 1135G7, 4C8T, up to 4.2 GHz Intel Core™ i5 - 1145G7, 4C8T, up to 4.4 GHz Intel Core™ i7 - 1165G7, 4C8T, up to 4.7 GHz Intel Celeron 6305, 2C2T, 1.8 GHz Intel Celeron 6305E, 2C2T, 1.8 GHz
Memory	Two SO-DIMM DDR4 memory modules (1.2V, maximum support 64GB) , maximum frequency 3200MHz .
Graphics processing	Supports one VGA port with a maximum resolution of 1920x1080 @60Hz Supports one HDMI port with a maximum resolution of 3840 x 2160 @ 60Hz.
Network card	Supports 2 Intel processors 10/100/1000Mbit Ethernet
storage	One SATA 3.0 standard interface, one M.2 2280 SSD interface (PCIe x4)
PCIe	Supports one M.2 WIFI port (E-Key 2230 PCIe x1) Supports one M.2 4G/5G port (B-Key 3042/3052 USB2.0 & PCIe x1
USB	Supports 4 USB 3.0 ports and 4 USB 2.0 ports.
serial port	4 RS232 (3-wire), 2 RS232 (3-wire) / RS422 / RS485
IO	Supports 8 GPIOs and 1 SIM card slot (expandable, optional).
sound card	ALC662 High-Fidelity Sound Card (Line-Out , MIC-in)
power supply	+ 12V to + 19V voltage , + 12V is recommended. Power on (default) , trigger power on (optional) .
adapter	60W or above
temperature	Operating temperature : -20° C to + 60 ° C (-40° C to + 70 ° C is optional)
size	205 mm (length) x 140 mm (width) x 55 mm (height) (Overall dimensions excluding wall mount and external interface)
Heat dissipation	Fanless design
operating system	Windows 10 , Windows 11, Linux
weight	1.46 kg (bare machine) , 2.55 kg (including packaging)
color	The entire unit is blue, with black front and rear panels.